

Your nearest Merlo dealer



MERLO S.P.A.

Via Nazionale, 9 - 12010 S. Def. di Cervasca - Cuneo - Italia  
 Tel. +39 0171 614111 - Fax +39 0171 684101  
 www.merlo.com - info@merlo.com

STABILIZED TELEHANDLERS	P30.10	P35.11	TF35.11TT-145	P40.12	P40.12PLUS	P40.13	P40.13PLUS	P40.13CSTOP	P40.14	P40.14PLUS	P40.14CSTOP	P40.17	P40.17PLUS	P40.17CSTOP	P50.18PLUS	P50.18CSTOP
Max. capacity (kg)	3000	3500	3500	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000	5000	5000
Lifting height (m)	9,8	11	11	11,5	11,5	12,5	12,5	12,5	13,5	13,5	13,5	16,6	16,6	16,6	17,5	17,5
Operating weight (kg)	7600	9000	9100	9200	9200	9300	9300	9650	9950	9950	10300	11670	11670	12020	13300	13650
Standard tires	400/70-20	400/70-24	400/70-24	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-24	400/70-24	400/70-24	400/80-24	400/80-24
Width (mm)	2100	2310	2310	2240	2240	2240	2240	2240	2240	2240	2240	2420	2420	2420	2400	2400
Height (mm)	2120 (2020 L)	2530	2530	2425	2425	2425	2425	2425	2425	2425	2425	2500	2500	2500	2535	2535
Length (mm)	4700	5150	5150	5010	5010	5410	5410	5410	5750	5750	5750	5970	5970	5970	6190	6190
Boom side shift (mm)	-	+/- 310	+/- 310	+/- 330	+/- 330	+/- 340	+/- 340	+/- 340	+/- 345	+/- 345	+/- 345	+/- 435	+/- 435	+/- 435	+/- 445	+/- 445
Frame levelling (%)	-	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8
Engine	Kohler 2504 TCR	Kohler 2504 TCR	Deutz TCD3.6	Kohler KDI2504	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Perkins 904J	Perkins 904J
Stage V	DOC+DPF	DOC+DPF	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC
Displacement/Cylinders	2500/4	2500/4	3600/4	2500/4	3600/4	2500/4	3600/4	3600/4	2500/4	3600/4	3600/4	2500/4	3600/4	3600/4	3600/4	3600/4
Engine power (kW/HP)	55,4/75,1	55,4/75,1	105/143	55,4/75,1	85,9/116,8	55,4/75,1	85,9/116,8	100/136	55,4/75,1	85,9/116,8	100/136	55,4/75,1	85,9/116,8	100/136	85,9/116,8	100/136
EPD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Number of speeds	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Max. speed (km/h)	40	33	40	33	40	33	40	33	40	33	40	33	40	33	40	40
Hydraulic pump	LS+FS	LS + FS	LS + FS	LS	LS	LS	LS + FS	LS	LS	LS	LS + FS	LS	LS	LS + FS	LS	LS + FS
Flow/pressure (l/min - bar)	117 - 210	117 - 250	150 - 250	108 - 250	108 - 250	108 - 250	108 - 250	139 - 250	108 - 250	108 - 250	139 - 250	108 - 250	108 - 250	139 - 250	108 - 250	139 - 250
ASCS	Light	Light	Light	Light	Full	Light	Full	Full	Light	Full	Full	Light	Full	Full	Full	Full
ROPS - FOPS level II	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Cab suspension	-	-	-	-	-	-	●	-	-	-	●	-	-	●	-	●

ROTATING TELEHANDLERS	ROTO40.16	ROTO40.16S	ROTO40.18	ROTO40.18S	ROTO50.21	ROTO50.21S	ROTO50.21SPUS	ROTO50.26	ROTO50.26S	ROTO50.26SPUS	ROTO50.30S	ROTO50.30SPUS	ROTO70.24S	ROTO70.24SPUS	ROTO 50.35SPUS CVTRONIC	ROTO 70.285PLUS CVTRONIC
Max. capacity (kg)	4000	4000	4000	4000	4950	4950	4950	4950	4950	4950	4950	4950	7000	7000	4950	7000
Lifting height (m)	15,8	15,8	17,7	17,7	21	21	21	25,9	25,9	25,9	29,2	29,2	24,2	24,2	34	28
Operating weight (kg)	12900	13000	13500	13600	15800	15800	16500	16600	16600	17300	19800	20500	19500	20200	23350	22750
Standard tires	400/70-20	400/70-20	400/70-20	400/70-20	18-22,5	18-22,5	18-22,5	18-22,5	18-22,5	18-22,5	445/65 R22,5	445/65 R22,5	445/65 R22,5	445/65 R22,5	445/80 R 25	445/80 R 25
Width (mm)	2240	2240	2240	2240	2430	2430	2430	2430	2430	2430	2490	2490	2490	2490	2540	2540
Height (mm)	2980	2980	2980	2980	3120	3120	3120	3120	3120	3120	3160	3160	3160	3160	3325	3325
Length (mm)	6280	6280	6030	6030	6830	6830	6830	7150	7150	7150	7790	7790	7545	7545	8590	8310
Frame levelling (%)	-	+/-12, +/-4	-	+/-12, +/-4	-	+/-12, +/-4	+/-12, +/-4	-	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4	+/-12, +/-4
Engine	FPT F34	FPT F36	FPT F34	FPT F36	FPT F34	FPT NEF45	FPT NEF45	FPT F34	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45
Stage V	DOC+DPF	DOC+DPF+SCR	DOC+DPF	DOC+DPF+SCR	DOC+DPF	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR
Displacement/Cylinders	3400/4	3600/4	3400/4	3600/4	3400/4	4500/4	4500/4	3400/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4
Engine power (kW/HP)	55,4/75	90/122	55,4/75	90/122	55,4/75	125/170	125/170	55,4/75	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170
EPD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Number of speeds	2	2	2	2	2	2	2	2	2	2	2	2	2	2	CVTronic	CVTronic
Max. speed (km/h)	25	40	25	40	25	40	40	25	40	40	40	40	40	40	40	40
Hydraulic pump	LS + FS	LS + FS	LS + FS	LS + FS	LS + FS	LS + FS	2 - LS + FS	LS + FS	LS + FS	2 - LS + FS	LS + FS	2 - LS + FS	LS + FS	2 - LS + FS	2 - LS + FS	2 - LS + FS
Flow/pressure (l/min - bar)	103.5 - 250	103.5 - 250	103.5 - 250	103.5 - 250	103.5 - 250	138 - 250	138+100 - 250/230	103.5 - 250	138 - 250	138+100 - 250/230	138 - 250	138+100 - 250/230	138 - 250	138+100 - 250/230	158+100 - 260	158+100 - 260
ASCS	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full
ROPS - FOPS level II	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Tilting cab	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Turret rotation	415°	415°	415°	415°	600°	360° - Continuous	360° - Continuous	600°	360° - Continuous	360° - Continuous	360° - Continuous	360° - Continuous	360° - Continuous	360° - Continuous	360° - Continuous	360° - Continuous

CONCRETE MIXERS	DBM2500	DBM3500
Drum volume (l)	3500	5000
Concrete yield capacity (l)	2500	3500
Operating weight (kg)	7050	7400
Standard tires	405/70-20"	18-19,5"
Width (mm)	2300	2355
Height (mm)	2900	3100
Length (mm)	6220	6480
Max. unloading height (mm)	1760	2060
Water tank (l)	930	930
Bucket capacity (l)	700	700
Engine	Deutz TCD3.6	Deutz TCD3.6
Stage V	DOC+SCR+DPF	DOC+SCR+DPF
Displacement/Cylinders	3600/4	3600/4
Engine power (kW/HP)	74,4/100	74,4/100
EPD	●	●
Max. speed (km/h)	40	40
Drum rotation speed	0 ÷ 26	0 ÷ 18
ROPS	●	●
4WD and 4 steering wheel	●	●
Extension chute	2	2

TRACKED CARRIERS	CINGOM500	CINGOM700TD	CINGOM4.3EVO	CINGOM8.3TDEVO	CINGOM8.3EVO	CINGOM12.3EVO	M600TD-e
Max. capacity (kg)	500	700	400	800	800	1200	600
Engine (HP) - Battery	Honda - 5,5 Stage V	Honda - 12 Stage V	Yanmar - 24 Stage V	Kubota - 17 Stage V	Kubota - 17 Stage V	Kubota - 21 Stage V	Lithium 48 V / 7,5 kWh
Fuel	Petrol	Petrol	Diesel	Diesel	Diesel	Diesel	Electric
Electric starter	-	●	●	●	●	●	●
Max. speed (km/h)	3,5	2,5 - 4	5	4	4	5	3 - 5
Operating weight (kg)	230	480	750	510	510	720	500
Width (mm)	690	750	680	800	800	1000	753
Length (mm)	1471	1500	2098	1750	1640	1830	1560
Bucket capacity (l)	700	700	700	700	700	700	700
Rubber track dimensions	160 x 72 x 33	180 x 72 x 36	180 x 72 x 41	180 x 72 x 36	180 x 72 x 36	230 x 72 x 40	180 x 72 x 36
Transmission control	Hydraulic	Hydraulic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Electric
Transmission pump (cc)	3,2 + 3,2	4,27 + 4,27	13+13	11 + 11	11 + 11	13 + 13	-
Gearmotors	-	●	●	●	●	●	●
Operator platform	-	●	●	●	●	●	●
Hydraulic pump (cc)	-	6	8+2,5	8 + 2,5	8 + 2,5	8 + 2,5	3,5
Flow / pressure (l/min - bar)	-	20/180	23+7/180	23+7/180	23+7/180	23+7/180	8 / 150
Oil radiator	-	●	●	●	●	●	-
4WD and 4 steering wheel	2	4	6	6+2	6+2	6+2	2
Multifunction with quick coupling	-	-	-	●	●	●	-

# Product offer 2024

EU



